

TOMCO Pneumatic SINGLE SHUT-OFF

SERIES T4000, T400, PT400

INDUSTRIAL INTERCHANGE

3/8" BASIC SIZE

Working Range:
Maximum Operating Pressure;
To 250 psig
Temperature: -40° to +225° F
Pressure Drop:

Inlet	5 psig	10 psig	
	100 scfm	49 scfm	67 scfm



PLUG



AUTOMATIC COUPLER



MANUAL COUPLER



MANUAL COUPLER

FEMALE THREAD	Catalog No.	Catalog No.	Catalog No.	Catalog No.
1/4" NPTF	T41	T4000	T400	PT400
3/8" NPTF	T43	T4200	T420	PT420
1/2" NPTF	T45	T4400	T440	PT440

MALE THREAD	Catalog No.	Catalog No.	Catalog No.	Catalog No.
1/8" NPTF	T38	-	-	-
1/4" NPTF	T40	T4100	T410	PT410
3/8" NPTF	T42	T4300	T430	PT430
1/2" NPTF	T44	T4500	T450	PT450

HOSE STEM	Catalog No.	Catalog No.	Catalog No.	Catalog No.
1/4" HOSE I.D.	T46	T4600	T460	PT460
5/16" HOSE I.D.	T47	-	-	-
3/8" HOSE I.D.	T48	T4800	T480	PT480
1/2" HOSE I.D.	T49	T4900	T490	PT490
3/8" HOSE I.D. (Push-On)	T48P	T4800F	T480P	PT480P

REUSABLE HOSE CLAMP	Catalog No.	Catalog No.	Catalog No.	Catalog No.
HOSE I.D. X HOSE O.D.				
5/16" X 9/16"	TC5-4	C5-4	C5-40	PC5-40
5/16" X 5/8"	TC7-4	C7-4	C7-40	PC7-40
5/16" X 11/16"	TC9-4	C9-4	C9-40	PC9-40
3/8" X 9/16"	TD5-4	D5-4	D5-40	PD5-40
3/8" X 5/8"	TD7-4	D7-4	D7-40	PD7-40
3/8" X 11/16"	TD9-4	D9-4	D9-40	PD9-40
3/8" X 3/4"	TD11-4	D11-4	D11-40	PD11-40
3/8" X 13/16"	TD13-4	D13-4	D13-40	PD13-40
3/8" X 7/8"	TD15-4	D15-4	D15-40	PD15-40
1/2" X 7/8"	TP15-4	P15-4	P15-40	PP15-40
1/2" X 15/16"	TP17-4	P17-4	P17-40	PP17-40
1/2" X 1"	TP19-4	P19-4	P19-40	PP19-40

Sleeve lock option available on above couplers. See TOMCO Price List.